



TECHNICAL DATA SHEET
PART #5710-140
TUCSON DIRECT VENT MODEL 8700
ADDITION OF A PILOT SHIELD

TOOLS REQUIRED

Phillips Screwdriver

KIT #5710-140 COMPONENTS

1- PILOT SHIELD

1- INSTRUCTION SHEET

WARNING: Servicing of gas controls, appliances, systems and leak testing must be PERFORMED BY QUALIFIED PERSONNEL ONLY. GAS EXPLOSION HAZARDS ARE PRESENT.

BEFORE YOU BEGIN: *Turn the valve control to the off position. Turn off gas supply to the stove. Work only on a cold stove.*

PROCEDURE:

- 1) Locate and remove the screw that holds the door closed. Open the front door. Carefully remove the log set and the burner tube. Note their positions for reassembly.
- 2) Locate the pilot assembly. Remove the two screws used to mount the pilot assembly. Keep these screws.
- 3) Position the pilot shield on top of the pilot assembly, with the vertical portion of the shield toward the rear. Line up the holes on the “legs” of the pilot shield with those of the pilot assembly. This is shown in the Figure below.
- 4) Insert the two screws saved from step 3 into the holes of the pilot shield and pilot assembly and tighten.
- 5) Place the burner tube back into the stove. Be sure to line it up properly.
- 6) Place the log set in the stove. Once the log set and burner tube have been positioned appropriately in the stove, close the door and tighten the door screw.
- 7) Turn on the gas supply. **LEAK TEST BEFORE AND AFTER LIGHTING THE STOVE.**

