

Technical Data Sheet

Installation of the Sterling 5" X 8" Rear Exit Slider Starter Kit For Sterling Direct-Vent Model #8531 *Assembly 95-61223HB*

Date: 1/2/2003

Page: 1 of 1

KIT CONTENTS:

- (16)#4500-3435 - Screws 8-32 X 3/8" Type F PH
- (1)#3160-101 - 5" X 6-1/2" Gasket Ring
- (1)#3160-102 - 8" X 9-1/2" Gasket Ring
- (1)#5701-1223HB - 5" X 8" Horizontal Stove Adaptor (SLIDER)

TOOLS REQUIRED:

Phillips Screwdriver

PROCEDURE:

- 1) Locate and remove the temporary shipping screws from the inner collar mounting holes with a phillips screwdriver.
- 2) Place the 5" X 6-1/2" gasket ring onto the end of the inner (5") portion of the stove adaptor. Attach them to the stove with 8 of the screws provided.

HINT: Use Spray 'n Glue or liquid gasket glue to help hold the gasket rings in place during assembly.

- 3) Place the 8" X 9-1/2" gasket ring onto the end of the outer (8") portion of the stove adaptor. Attach them to the stove using the remaining 8 screws.

Follow the installation instructions provided with minimum vent kit (kit #95-65000). Make sure all stove and termination clearances outlined in the Owner's Manual are observed.